





CORDAGE PREPARATION

MAXIMUM JACKET O.D. ACCEPTED BY EXTERNAL STRAIN RELIEF = 9 DIA (0.354")
 MAXIMUM JACKET O.D. ACCEPTED BY INTERNAL STRAIN RELIEF = 9 DIA (0.354")
 MAXIMUM CONDUCTOR SIZE ACCEPTED BY TERMINALS = 2.5 mm² (14 AWG)

CORDAGE PREPARATION

CONDUCTOR INSULATION COLOR	CONDUCTOR COLOR CODE	"LENGTH"	"STRIP"
GREEN/YELLOW	GROUND	15	8
BLUE	NEUTRAL	25	8
BROWN	LINE	25	8



SPECIFICATIONS

TEMPERATURE RATING	300°C (572°F)
CURRENT RATING	25 AMPERE
VOLTAGE RATING	220/380 VOLT
CONTACTS	2 POLE 3 WIRE GROUNDING
STANDARD	-
MATERIALS	- RED SILICONE RUBBER HEAD - BLACK RUBBER COVER
REMARKS	STRAIGHT STYLE BODY WITH INTEGRAL STRAIN RELIEF
NOTE	SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

ALL DIMENSIONS ARE IN MILLIMETERS

TITLE
 ROUND PIN BAND HEATER CONNECTOR, SILICONE RUBBER, RED BODY, BLACK COVER

SCALE NONE	DATE 10-05-2007	PART NO. 111-10341	REV -
---------------	--------------------	-----------------------	----------